


- Constant current charger for NiMH/NiCd batteries
- For 50 mAh – 1 Ah batteries
- Thermal fuse in transformer, protected against reversed polarity and short circuit proof
- Plug-in unit
- LED indicates charging
- Exchangeable DC plugs
- Konstantstrømlader for NiMH/NiCd-batterier
- For 50 mAh – 1 Ah batterier
- Termosikring i transformator, polvendings- og kortslutningssikker
- Plugg-inn enhet
- Lysdiode indikerer lading
- Utskiftbare DC plugger


Technical specifications
Tekniske data

Input voltage:	Inngangsspenning:	230 VAC +6/-10%, 50/60Hz
Charging voltage (1-12 cells simultaneously):	Ladespenning (1-12 celler samtidig):	Max. 30 V
Charge current - constant:	Ladestrøm - konstant:	60 mA
Temperature range:	Temperaturområde:	-10°C - +40°C
Current limiting:	Strømbegrensning:	Ja / Yes
Insulation class:	Isolasjonsklasse:	II
Electrical safety standard:	Elektrisk sikkerhetsstandard:	EN 60065, EN 60950
EMC standards	EMC standarder	
• Emission:	• Emisjon:	EN 61000-6-3
• Immunity:	• Immunitet:	EN 61000-6-1
Output terminals	Utgangsterminaler	
• Cord with/without plug:	• Sek. ledning med/uten plugg:	Tilbehør / Accessories
Dimensions without plug (LxWxH):	Mål uten plugg (LxBxH):	75 x 47 x 49 mm
Weight:	Vekt:	220 g

Versions / Versjoner

	14 h charging - battery capacity 14 t lading - batterikapasitet
5 mA	50 mAh
10 mA	100 mAh
15 mA	150 mAh
25 mA	250 mAh
30 mA	300 mAh
35 mA	350 mAh
45 mA	450 mAh
50 mA	500 mAh
60 mA	600 mAh
80 mA	800 mAh
90 mA	900 mAh
100 mA	1 Ah