

SPECIFICATIONS FOR 9061	12 / 5	12 / 6	12 / 7,5	12 / 9	24 / 6
Available versions	x				
Input voltage (VDC):	8-16	10-16			20-32
Output voltage (VDC)	5	6		7,5	9
Max. current (A) • Continuous	1	3			1.5
Max. Current (A) • Intermittent	1.4	4			3
Max. output power • Continuous	27 W				
Max. output power • Intermittent	40 W				
• Continuous (-20°C - +25°C)	2,0 A				
• Intermittent	3,0 A				
• Linearly derating to (at +60°C)	1,0 A				
Load regulation (0-2,0 A load and 24 VDC input voltage)	< 5,0%				
Line regulation (20-32 V input and 2 A load)	< 5,0%				
No load current approx.	8 mA				
Temperature range	-20°C - +25°C				
EMC, emission:	EN 61000-6-3				
EMC, Immunity:	EN 61000-6-1				
Dimensions:	70,5 × 105 × 46 mm				
Weight:	250 g				

SPECIFICATIONS FOR 9061	24 / 7,5	24 / 9	24 / 12	24 / 12 (backup)
Available versions	x			
Input voltage (VDC):	20-32			
Output voltage (VDC)	7.5	9	13.5	13,5 (14,5 backup)
Max. current (A) • Continuous	1.6	1.7	2	
Max. Current (A) • Intermittent	3			3 (1 A backup)
Max. output power • Continuous				
Max. output power • Intermittent				
• Continuous (-20°C - +25°C)				
• Intermittent				
• Linearly derating to (at +60°C)				
Load regulation (0-2,0 A load and 24 VDC input voltage)				
Line regulation (20-32 V input and 2 A load)				
No load current approx.				
Temperature range				
EMC, emission:				
EMC, Immunity:				
Dimensions:				
Weight:				