

	5V	9V	12V
Available versions	x		
Input voltage	90 - 264VA 0.3A Max	90 - 264VA 0.3A Max	90 - 264VA 0.4A Max
Line frequency	47 - 63Hz		
Output voltage	5V \pm 5%	9V \pm 5%	12V \pm 5%
Max output power	5W	7.2W	7.2W
Min./Max. output current (CC limitation, foldback when Vout < 60%)	0A/1.0A (1A-1.3A when Vout > 3V)	0A/0.8A (0.8A-1.0A when Vout > 6V)	0A/0.6A (0.6A-0.8A when Vout > 8V)
Load regulation (0 - 100% load. Measured on PSB)	< 1%	< 1.5%	< 1%
Mains regulation: (Mains variation: 90 - 264V, 100% load)	< 0,5%		
Switching frequency Ripple (measured on PCB)	< 120mV p-p		
Average Efficiency (at 100% load, 230V) approx.	>80.5%		
Efficiency level VI & EU CoC Tier 2	Yes		
Switch frequency approx.	20-30kHz		
Overshoot (90 - 10% load variation)	< 200mV	< 250mV	< 300mV
Undershoot (10 - 90% load variation)- :Measured on pcb	< 250mV	< 250mV	< 300mV
Hold up time (Vout down to 90%) at 230VAC	> 50ms	> 80ms	> 80ms
Temperature range	- 25 til +40oC		
null	- 25 til +85oC		
Derating	1W/oC over 40oC		
Safety	EN 60601-1 3.1		
Insulation class	Class II		
Insulation voltage: Primary – secondary	4000VAC / 5700VDC		
EMC standards	61000 -6-1 & -6-3; 60601-1-2 Ed.4; FCC 15B		
Standby power	<0.075W		
IP-degree	IP4X		
Input terminal	2-pins IEC320 C8 connector		
Output terminals	Modular 4P4C (RJ22), USB or cable with/without plug.		
Dimensions	86 x 50 x 29mm		
Weight without DC-cable and mains adapter	75g.		