

SPECIFICATIONS FOR 2284	12 V	24 V
Available versions	x	x
Input voltage (VDC):	10-15 VDC	20-30 VDC
Output power: (W)	150	150
Output power (W), intermittent:	300	300
Output voltage (VDC):	230 VAC +5/-10% (50 Hz)	230 VAC +5/-10% (50 Hz)
Temperature range • Operating:	0° C - 50° C	0° C - 50° C
No load current:	<0,5A	< 0,4 A
Output wave form:	Pure sine wave / Ren sinus	Pure sine wave / Ren sinus
Efficiency:	>90%	>90%
Low battery alarm:	10,7 V	21,4 V
Low battery shut-down:	10 V	20 V
Electrical safety standard:	EN 60950	EN 60950
EMC • Emission:	EN 61000-6-3	EN 61000-6-3
EMC • Immunity:	EN 61000-6-1	EN 61000-6-1
Protection:	Input low voltage, input overvoltage, low battery alarm, overtemperature, overload protection and short circuit proof, Cooling fan	Input low voltage, input overvoltage, low battery alarm, overtemperature, overload protection and short circuit proof, Cooling fan
MTBF:	2284: 63.000 h/ t	2284: 63.000 h/ t
DC terminals:	Fixed cable w. battery clips	Fixed cable w. battery clips
Dimensions (L×W×H):	190 × 152 × 66 mm	190 × 152 × 66 mm
Dimensions mounting holes:	110 × 145 mm	110 × 145 mm
Weight:	1,15 kg	1,15 kg