

SPECIFICATIONS FOR 3743 LA	6 V	12 V	24 V	36 V	48 V
Available versions		x			
Input voltage: / Line frequency	90 - 264VAC / 47 - 63Hz				
Max output power	11 W	14.7 W	16.5 W	17.6 W	
Step 0 < 30min Yellow	CC 100mA ± 25mA, Vbat < 5V.	CC 100mA ± 25mA, Vbat < 10.5V.	CC 100mA ± 25mA, Vbat < 21V.	CC 100mA ± 25mA, Vbat < 31.5V.	CC 100mA ± 25mA, Vbat < 42V.
Step 0 > 30min Red (4 blinks)	0A / 0V				
Step 1 (Constant Current) Yellow	CC 1.5A ± 5%, 5V < Vbat < 7.35V.	CC 1A ± 5%, 10.5V < Vbat < 14.7V.	CC 0.56A ± 5%, 21V < Vbat < 29.4V.	CC 0.4A ± 10%, 31.5V < Vbat < 44.1V.	CC 0.3A ± 5%, 42V < Vbat < 58.8V.
Step 2 (Constant Voltage) Flashing Yellow	CV 7.35V ±0.1V, Ich<400mA or 4h.	CV 14.7V ±0.1V, Ich<250mA or 4h.	CV 29.4V ±0.1V, Ich<150mA or 4h.	CV 44.1V ±0.1V, Ich<100mA or 4h.	CV 58.8V ±0.1V, Ich<100mA or 4h.
Charge timer (step2, CV)	4h				
Safety timer (all steps) Red (5 blinks)	72h				
Step 3 (Maintenance voltage) Green	6.85V	13.7V	27.4V	41.1V	54.8V
Restart voltage	6.5V	13.0V	26.0V	39.0V	52.0V
Efficiency (at 100% load) approx.:	80%	82%	84%		
No load consumption	< 0,5 W				
Switch frequency approx.:	56kHz				
Ripple:	< 100mV p-p				
Formation Charge (Step 0)	Low current start-up of deeply discharged battery.				
Float charge:	Pulses at safe float voltage level for maximum topping of battery capacity.				
Indication when "Battery not connected"	Flashing Green (1s/1s)				
Leakage current from battery with mains switched off:	< 300 µA at nominal battery voltage (< 0.22 Ah/month)				
Protection:	Protected against reversed polarity. Error Indication: Red (2 blinks) Short circuit proof. Error Indication: Red (3 blinks) Charging of wrong lower voltage battery pack will be limited to 100mA and terminated after 30min. Indication: Red (4 blinks) Safety timer. Error Indication: Red (5 blinks) No charge (or charge terminated) if connecting wrong battery pack with higher voltage. Indication: LED is OFF.				
Temperature range:	Operating: ±25 to +40oC. Storage: ±25 to +85oC				
Safety:	Medical EN 60601-1 / Home Healthcare EN 60601-1-11 (VNOM≥110VAC) / Battery Charger EN 60335-2-29				
Insulation class :	Class II				
Insulation voltage: Primary – secondary:	4000VAC / 5700VDC				
EMC standards:	EN 55014-1 and –2, EN 61000-6-3, EN 61000-6-1, EN 60601-1-2				
Input terminal:	2-pins IEC 320 connector for exchangeable mains plug (EU, US, UK and AUS) or mains cord with C7 connector.				
Output terminals:	Cord with/without plug. Exchangeable plugs available.				
IP-Grade:	IP41				
Rec. battery capacity:	7.5Ah (C/5) to 20Ah (<400mA charge current as EoC detection) or up to 75Ah (utilizing the 4h CV timer as EoC detection)	5Ah (C/5) to 12.5Ah (<250mA charge current as EoC detection) or up to 50Ah (utilizing the 4h CV timer as EoC detection)	2.8Ah (C/5) to 7.5Ah (<150mA charge current as EoC detection) or up to 28Ah (utilizing the 4h CV timer as EoC detection)	2.0Ah (C/5) to 5Ah (<100mA charge current as EoC detection) or up to 20Ah (utilizing the 4h CV timer as EoC detection)	1.5Ah (C/5) to 5Ah (<100mA charge current as EoC detection) or up to 15Ah (utilizing the 4h CV timer as EoC detection)
Dimensions:	108,5 × 49 × 29,3 mm				
Weight:	150g				