


9980

Max. 24 VA

AC/AC DESKTOP

- Max 24 VA output power
- 230 VAC input voltage
- Available with EU or UK terminals
- Compliance with relevant worldwide safety standards
- Exchangeable output plugs, providing:
 - reduced stocking requirements
 - short delivery lead times
 - snap-locks for added safety



| <u>Technical specifications</u> | 9 V | 12 V | 24 V | 24 V |
|--|---------------------------------|-------------|-------------|-------------|
| <i>Input voltage:</i> | 230 VAC, 50 Hz | | | |
| <i>Output voltage:</i> | 9VAC | 12VAC | 24VAC | 24VAC |
| <i>Max. output power:</i> | 9VA | 12VA | 12VA | 24VA |
| <i>Max. Load current:</i> | 1A | 1A | 0,5A | 1A |
| <i>Temperature range:</i> | -10°C to +40°C | | | |
| <i>Protection:</i> | Thermal fuse in primary | | | |
| <i>Insulation class</i> | II | | | |
| <i>Electrical safety</i> | EN 60950 | | | |
| <i>EMC, Emission</i> | EN 61000-6-3 | | | |
| <i>EMC, Immunity</i> | EN 61000-6-1 | | | |
| <i>Mains connections:</i> | EU or UK | | | |
| <i>Output terminals:</i> | Secondary cable w/snap-on plugs | | | |
| <i>Dimensions: EU+UK</i> | 81x56x49mm | | | |
| <i>Weight: UK</i> | 540g | 560g | 540g | 680g |
| <i>Weight: EU</i> | 490g | 500g | 500g | 620g |

19062006

www.mascot.no
sales@mascot.no
Main Office
 PO Box 177
 N-1601 FREDRIKSTAD
 NORWAY
 Phone: +47 69 36 43 00
 Fax: +47 69 36 43 01

Mascot UK
 Box 2090, Salisbury
 Wiltshire SP2 2BH
 UK
 +44 1722 504 853
 +44 845 299 1210

Mascot DE-AT-CH-BENELUX
 Hirschbergstr. 28/7
 D-74838 LIMBACH
 GERMANY
 +49 6287 95140
 +49 6287 95141
 Tettlinger Str. 52
 D-88239 WANGEN
 GERMANY
 +49 7528 951677
 +49 7528 951678

Mascot France
 38 rue Leo Lagrange
 94270 Le Kremlin Bicêtre
 FRANCE
 +33 1 46 58 71 85
 +33 1 46 58 71 85